

Sonae Arauco: NAF-Hersteller von MDF und Holzfaserdämmstoffen

Seit dem 03.12.2009 ist die Sonae Arauco Deutschland GmbH (ehemals Glunz AG), Meppen/D als sogenannter NAF-Hersteller von MDF (Mitteldichten Faserplatten) und Holzfaserdämmstoffen anerkannt. Dies wurde dem Unternehmen von dem kalifornischen Air Resources Board (ARB), Sacramento/USA bescheinigt.

NAF ist die Abkürzung für **No-Added Formaldehyde** und bedeutet, dass für die Herstellung bestimmter MDF-Produkte **keine formaldehydbasierenden Bindemittel** eingesetzt werden.

Um eine entsprechende Bescheinigung zu erhalten, muss die Zertifizierung durch eine vom ARB anerkannte Stelle (engl.: TPC = **Third Party Certifier**) vorliegen. Als TPC der Sonae Arauco Deutschland GmbH fungiert die Materialprüfanstalt in Eberswalde/D.

Derzeit stellt NAF den **höchstmöglichen Standard bezüglich Formaldehydemission** bei Holzwerkstoffen dar. Neben NAF gibt es noch weitere Standards, wie z.B. CARB 2 (USA) oder F**** (Japan), die international Anwendung finden. Die folgende Tabelle zeigt einen Vergleich zwischen CARB 2 und NAF.

Standard	Erläuterung	Grenzwerte [ppm]
CARB 2 ¹⁾	seit 2011 in Kraft: momentan für Kalifornien verbindlich; wird vorzugsweise in Europa für Lieferungen in die USA verwendet	0,11
NAF	der derzeit höchstmögliche Standard bezüglich Formaldehydemission	0,03
	Messwerte Sonae Arauco	0,01

Die NAF-Bescheinigung von Sonae Arauco bezieht sich auf folgende Produkte in den Stärkenbereichen **8 bis 80 mm**:

Innovus Coloured MDF Black Ecoboard	Innovus Coloured MDF Black Fire X Ecoboard	Agepan DWD protect	Agepan THD Putz 050
Innovus Coloured MDF Terra Ecoboard	MDF Fire X Ecoboard	Agepan DWD 600	Agepan THD max
Innovus Coloured MDF Curry Ecoboard	MDF ST Ecoboard	Agepan DWD black	Agepan THD Static
Innovus Coloured MDF Royal Ecoboard	MDF Novolac Ecoboard	Agepan UDP	Agepan THD 180
Innovus Coloured MDF Berry Ecoboard	MDF Ultralight Ecoboard	Agepan THD Install	Agepan TEP
Innovus Coloured MDF Sand Grey Ecoboard	MDF Sports Flooring Ecoboard	Agepan THD N+F	3DF

Weitere Details können Sie dem beigefügten **Executive Order N-21-030** entnehmen.

Ausführliche Informationen finden Sie auch auf der Website des ARB unter www.arb.ca.gov.

¹⁾CARB = Californian Air Resources Board



Approval of Exemption of Third Party Certification No-added formaldehyde-based resin (NAF)

No.31/21/3433/02

MPA | Eberswalde

Materialprüfanstalt
Brandenburg GmbH

Prüfung, Überwachung,
Zertifizierung, Gutachten,
Forschung und Entwicklung

In compliance with the Formaldehyde Standards for Composite Wood Products Act, Title VI to the toxic Substances Control Act (TSCA) – Final rule 40 CFR Part 770 it has been stated that the product

Alfred-Möller-Straße 1, H 13
D-16225 Eberswalde

Fon +49 (0) 33 34. 65 560
Fax +49 (0) 33 34. 65 550

www.mpaew.de
office@mpaew.de

Geschäftsführer:
Dr. Peter Schumacher

HRB 10408 FF

Type: MDF

Product name: MDF Ultralight Ecoboard, MDF ST Ecoboard, MDF Sports Flooring Ecoboard, Innovus Coloured MDF Black Ecoboard, Innovus Coloured MDF Terra Ecoboard, Innovus Coloured MDF Curry Ecoboard, Innovus Coloured MDF Royal Ecoboard, Innovus Coloured MDF Berry Ecoboard, Innovus Coloured MDF Grey Ecoboard, Innovus Coloured MDF Sandgrey Ecoboard, Agepan DWD CE, Agepan DWD protect, Agepan THD N+F, Agepan THD 180, Agepan DWD 600, Agepan UDP, Agepan THD Static, Agepan THD Putz 050, Agepan THD max, Agepan DWD black, Agepan THD Install, MDF Fire X Ecoboard, Innovus Coloured MDF Black Fire X Ecoboard, MDF Novolac Ecoboard, 3DF

Thickness range: 0,19 to 3,15 inch

produced by the manufacturer

Sonae Arauco Deutschland GmbH
Grecostraße 1, 49716 Meppen, Germany

in the plant

Sonae Arauco Deutschland GmbH, plant Meppen
Grecostraße 1, 49716 Meppen, Germany

is exempt from the testing requirements in § 770.15 and certification requirements in §§ 770.20 and 770.40(b) according to

§770.17 No-added formaldehyde-based resins.


The approval is based on and only valid in combination with the California Air Resources Board (CARB) Executive Order no. N-21-030 of 15th of November 2021. All requirements, terms and conditions stated in N-21-030 must be met.

The unique approval ID is: **TPC-RTA-352864**

This approval is effective until 15th of November 2023, subject to valid CARB Executive Order no. N-21-030.

Eberswalde, 16th of November 2021




Dr. Robby Wegner
Head of Certification Body

Sparkasse Schwandorf
Kto-Nr.: 100 164 862
BLZ: 750 510 40
IBAN: DE55 7505 1040 0100 1648 62
BIC-/SWIFT: BYLADEM1SAD
USt.-Id. DE814335485
Finanzamt Eberswalde



Die Akkreditierung gilt nur für die in der Urkunde aufgeführten Verfahren.



EC notified 0763



CARB notified TPC 18

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER N-21-030

Relating to CARB Approval to Use No-added Formaldehyde Resins by
Composite Wood Product Manufacturers under
section 93120.3, title 17, California Code of Regulations

Sonae Arauco Deutschland GmbH

Whereas, the California Air Resources Board (CARB) has adopted the "Airborne Toxic Control Measure to Reduce Formaldehyde Emissions from Composite Wood Products" (ATCM, title 17, California Code of Regulations, sections 93120-93120.12), which establishes formaldehyde emission standards for composite wood products;

Whereas, section 93120.1(a)(29) of the ATCM defines "no-added formaldehyde" (NAF) based resins to mean resins formulated with NAF as part of the resin cross-linking structure for making hardwood plywood (HWPW), particleboard (PB), medium density fiberboard (MDF), or thin medium density fiberboard (tMDF) including, but not limited to resins made from soy, polyvinyl acetate, or methylene diisocyanate;

Whereas, section 93120.3(c) of the ATCM allows manufacturers of HWPW, PB, MDF, and tMDF who use NAF-based resins to apply for written approval from the Executive Officer for an exemption from the requirements of section 93120.3(b) of the ATCM;

Whereas, section 93120.3(c) of the ATCM allows manufacturers of HWPW, PB, MDF, and tMDF who use NAF-based resins to submit an application for an exemption from the requirements of section 93120.3(b) of the ATCM to the Executive Officer, which includes: (A) a statement indicating which product types will be manufactured using NAF-based resins for sale in California; (B) the chemical formulation of the candidate NAF-based resins, including base resins, catalysts, and other additives used in manufacturing; (C) the name of their CARB-approved third-party certifier (TPC); and (D) data on emissions performance of the candidate NAF-based resins;

Whereas, the data on emissions performance of the candidate NAF-based resin required in section 93120.3(c) of the ATCM must be obtained by working with a CARB-approved TPC, and must include three months of routine quality control testing data, the correlation of the routine quality control testing data to primary or secondary testing data, and the results of one primary or secondary method test, as required in Appendix 2 of section 93120.12 of the ATCM;

Whereas, section 93120.3(c)(1) of the ATCM requires that 90 percent of the three months of routine quality control testing data and the results of one primary or secondary method test must be shown to be no higher than 0.04 parts per million (ppm), and that all data must be shown to be no higher than 0.05 ppm for HWPW and 0.06 ppm for PB, MDF, and tMDF;

Whereas, section 93120.3(c)(4) of the ATCM provides that the Executive Officer shall approve the application and issue an Executive Order if the evidence submitted by the applicant is sufficient to demonstrate that the applicant has met the requirements specified in section 93120.3(c)(1) of the ATCM;

Whereas, Glunz AG Meppen (Glunz AG or the applicant) submitted an original application that we received on September 30, 2009;

Whereas, the application from Glunz AG specifies the range in product manufacturing parameters, applicable post-press product treatments, base resin trade name(s) and base resin manufacturer(s)/supplier(s), and other ingredients added to the base resin by the applicant to manufacture NAF MDF and tMDF products;

Whereas, CARB was provided base resin/adhesive information specifying the base resin polymer type and minimum and maximum values of all major and any minor ingredients in the base resin on a percent weight of solids basis;

Whereas, the base resin/adhesive information was provided to CARB by Glunz is set forth in Confidential Attachment A;

Whereas, section 93120.3(c) of the ATCM allows NAF product manufacturers to apply for re-approval by CARB by submitting an updated application;

Whereas, Glunz AG submitted the original and the updated applications for approval to CARB as follows:

Executive Order #	Received Date	Signed Date	Actions
N-09-030	09/30/2009	12/03/2009	Original
N-09-030A	08/13/2010	10/21/2010	Amendment: request to modify the list of product names and the product types authorized
N-11-030	11/17/2011	12/20/2011	Renewal
N-11-030A	05/29/2012	06/14/2012	Amendment: request to modify the list of product types authorized
N-14-030	01/29/2014	06/06/2014	Renewal
N-14-030A	05/12/2015	05/21/2015	Amendment to modify the names of product types authorized

Executive Order #	Received Date	Signed Date	Actions
N-16-030	08/12/2016	09/20/2016	Renewal
N-18-030	07/17/2018	09/11/2018	Renewal and a request to change the name from "Glunz AG Meppen" to "Sonae Arauco Deutschland GmbH" (Sonae Arauco Deutschland or the applicant) and add a new resin system
N-20-030	07/17/2018	06/24/2020	Renewal and request to change product names
N-20-030A	09/24/2020	10/13/2020	Amendment: to add a new resin system
N-20-030B	05/10/2021	07/13/2021	Amendment: to add a new resin system

Whereas, Sonae Arauco Deutschland submitted an updated application for re-approval and amendment to add a new product to CARB on September 15, 2021;

Whereas, the updated application from Sonae Arauco Deutschland was deemed complete on October 13, 2021;

Whereas, the Executive Officer finds that the completed, updated application demonstrated the NAF manufacturer's ability to continue to comply with section 93120.3(c) of the ATCM; and

Whereas, the Executive Officer approved Sonae Arauco Deutschland's request for reapproval and it is appropriate that Executive Order N-20-030B be superseded by this Executive Order N-21-030.

Now, therefore, it is ordered that Sonae Arauco Deutschland is hereby approved as a NAF manufacturer of MDF and tMDF exempt from the requirements of section 93120.3(b) and Appendix 2 of section 93120.12 of the ATCM, provided that the following terms and conditions are met for products sold, supplied, offered for sale, or manufactured for sale in California:

1. Sonae Arauco Deutschland must use the commercial resin listed and supplier listed in Section A of Confidential Attachment A for the manufacture of NAF MDF and tMDF products.
2. As specified in Section B of Confidential Attachment A, Sonae Arauco Deutschland is legally responsible for ensuring that the base resin specifications are within the ranges specified in the original application and any subsequent amendments of this Executive Order.

3. The application rate of the base resins used for the manufacture of NAF composite wood products by Sonae Arauco Deutschland must be within the ranges specified in Section C of Confidential Attachment A of this Executive Order.
4. Other chemical components of the base resins (such as sizing wax and release wax) used for the manufacture of NAF composite wood products by Sonae Arauco Deutschland must be within the ranges specified in Section D of Confidential Attachment A of this Executive Order.
5. The allowable operating parameters for press temperature and press time for the base resins used to manufacture the NAF composite wood products by Sonae Arauco Deutschland must be within the ranges specified in Section E of Confidential Attachment A of this Executive Order.
6. Only the composite wood products with the product names listed in Section F of Confidential Attachment A of this Executive Order are authorized under this Executive Order.

Be it further ordered that this Executive Order N-21-030 supersedes Executive Order N-20-030B, which was signed on July 13, 2021.

Be it further ordered that Sonae Arauco Deutschland may change the resin system supplier listed in Section A of Confidential Attachment A if the new resin supplier supplies the same resin constituent listed in Confidential Attachment A of this Executive Order, at least one primary or secondary method test is performed on random samples selected by their CARB-approved TPC, and the Chief of the Risk Reduction Branch within the Transportation and Toxics Division is notified before Sonae Arauco Deutschland uses the resin for production.

Be it further ordered that Sonae Arauco Deutschland must conduct confirmatory testing for any new resin supplier by demonstrating that the results of one primary or secondary method test for the new resin system supplier are no higher than 0.04 ppm for the NAF products authorized under this Executive Order.

Be it further ordered that section 93120.3(c)(6) of the ATCM, as applicable, specifies that if the applicant decides to change to a formaldehyde-based resin system, the applicant must notify CARB in advance of changing resin systems and must comply with the requirements of section 93120.3(b) of the ATCM for that product type.

Be it further ordered that this Executive Order shall have a duration of two years and the applicant may apply for re-approval as provided in section 93120.3(c)(4) of the ATCM.

Be it further ordered that the applicant must maintain records in electronic or hard copy form for two years, for review by CARB upon request, as specified in section 93120.3(g) of the ATCM.

Be it further ordered that the Executive Officer may review and, for good cause, modify or revoke this Executive Order as provided in section 93120.3(c)(4) of the ATCM. The Executive Officer shall not modify or revoke this Executive Order without affording the applicant the opportunity for a hearing in accordance with the procedures specified in title 17, California Code of Regulations, section 60055.1 et seq.

Be it further ordered that the applicant must notify the Executive Officer in writing within 30 days of any change in their product manufacturing parameters or base resin manufacturer(s) or supplier(s) that constitute a modification outside the scope of their application for reduced testing under or an exemption from the requirements in section 93120.3(b) of the ATCM.

Executed at Sacramento, California on this 15th day of November 2021.



Robert Krieger, Chief
Risk Reduction Branch
Transportation and Toxics Division

Confidential

Attachment A
Formulation Data and Operating Parameters
Page 3 of 3

State of California
AIR RESOURCES BOARD
Executive Order N-21-030

Sonae Arauco Deutschland GmbH

Section F.

Product Names & Types Authorized in Executive Order N-21-030:

- MDF Ultralight Ecoboard, MDF ST Ecoboard, MDF Sports Flooring Ecoboard, Innovus Coloured MDF Black Ecoboard, Innovus Coloured MDF Terra Ecoboard, Innovus Coloured MDF Curry Ecoboard, Innovus Coloured MDF Royal Ecoboard, Innovus Coloured MDF Berry Ecoboard, Innovus Coloured MDF Grey Ecoboard, Innovus Coloured MDF Sandgrey Ecoboard, Agepan DWD CE, Agepan DWD protect, Agepan THD N+F, Agepan THD 180, Agepan DWD 600, Agepan UDP, Agepan THD Static, Agepan THD Putz 050, Agepan THD max, Agepan DWD black, Agepan THD Install, MDF Fire X Ecoboard, Innovus Coloured MDF Black Fire X Ecoboard, MDF Novoloc Ecoboard, 3DF - MDF and tMDF
 - thickness range = (0.19 to 3.15 inches)